

DECLARATION OF PERFORMANCE

IP-MF/2018/001

based on Test Report No LZFO1-01607/18/Z00NZP

according EN 13165+A2; 2016-08

Product type:	InnoPan PIR MF/THERM
Intended use:	Thermal Insulation for building or industrial installations
Additional information:	APIR thermal isolation board covered on both side with aluminium layer. IMPORTANT! Product application according relevant standards
Manufacturer:	InnoPan Tech Gyártó és Kereskedelmi Kft. 2040 Budaörs, Kamaraerdei út 2.
Place of production:	InnoPan Tech Gyártó és Kereskedelmi Kft. 8300 Tapolca, Keszthelyi út
Authorised representative:	InnoPan Tech Gyártó és Kereskedelmi Kft. 2040 Budaörs, Kamaraerdei út 2.
Notified body:	ITB® Instytut Techniki Budowlanej, identification Nr: 1488
Harmonised standard:	EN 13165+A2:2016-08

Essential properties	Declared Performance	Standard
• Thermal resistance:	$R_0 = 3,65 \text{ m}^2\text{K/W}$ (80 mm) Intermediate values may be calculated: $R_d = \text{nominal thickness} / \lambda_D$ (rounded to nearest 0,05)	EN 12667:2002
• Thermal conductivity:	$\lambda_0 = 0,022 \text{ W/(mK)}$ at nominal thickness $d_n = 20\text{-}200 \text{ mm}$	EN 12667:2002
Dimension stability under specified temperature and humidity conditions.	DS (70,90)3; relative length and width change $\leq 2\%$; relative thickness change $\leq 6\%$	EN 1604:2013-07
Dimension stability under specified temperature:	DS (-20,-12); relative length and width change $\leq 0,5\%$; relative thickness change $\leq 2\%$	EN 1604:2013-07
Compressive strength:	$\geq 120 \text{ kPa}$	EN 826/2013-07
Tensile strength:	$\geq 80 \text{ kPa}$	EN 1607/2013-07
Reaction to fire:	Class E	EN 13501-1
Durability of reaction to fire against heat, weathering, ageing / degradation:	The reaction of fire does not change over time.	

DECLARATION OF PERFORMANCE

IP-AL/2018/001

based on Test Report No LZF01-01607/18/Z00NZP

according EN 13165+A2; 2016-08

Essential properties	Declared Performance	Standard
Thickness/thickness tolerance:	20-200mm $d_N > 040 \text{ mm } \pm 2 \text{ mm}$ $40 \text{ mm} \leq d_N \leq 100 \text{ mm } \pm 3 \text{ mm}$ $d_N > 100 \text{ mm } + 5 \text{ mm } / - 3 \text{ mm}$	EN 13165
Density:	$\geq 32 \text{ kg/m}^3$	PN-EN 1602:2013-07
Short term water absorption:	No performance determined	
Flatness after one sided wetting:	No performance determined	
Water vapour permeability:	No performance determined	
Acoustic absorption permeability:	No performance determined	
Continous glowing combustion:	No performance determined	
Release of hazardous substances:	Harmonised testing method not available	

The performance of the product identified above is in conformity with the declared performace[s]. System of AVCP: 3 This declaration of performance is issued in accordance with Regulation 305/2011/EU, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

Budaörs, 01. 01. 2020.



INNOPAN TECH KFT. (1)
 2040 Budaörs, Kamaraerdei út 2.
 Adószám ~~25327364-2-13~~
 Bankszámlaszám.
 11600006-00000000-73744919
 Zoltán Németh Managing Director